



MindReader für Outlook

Installing a company license



Downloads MindReader for Outlook is being continuously further developed. You can find the current user documentation on our website in the following area: ⇒ ["Downloads | MindReader for Outlook"](#)

Contact STAR Group Headquarters:
STAR AG · Wiesholz 35 · 8262 Ramsen · Switzerland
www.star-group.net · info@star-group.net
Telephone +41 (0) 52 742 92 00 · Fax +41 52 742 92 92

STAR Language Technology & Solutions GmbH
Umberto-Nobile-Straße 19 · 71063 Sindelfingen · Germany

STAR Group is represented globally with 50 locations in over 30 countries. You can find your local STAR subsidiary on our website under ⇒ ["Company | STAR Group worldwide"](#).

Copyright, liability and trademarks © 2016 STAR Group. All rights reserved. All wording and images contained in this document are protected by copyright and may only – in whole or in part – be reproduced, processed, passed on to third parties or published with written permission from STAR AG. If you would like to use the content of this document, please contact info@star-group.net.

The content of this document has been carefully checked. STAR AG cannot be held liable for any consequences arising from the use of this documentation.

The trademarks used within this document are the property of their respective rights holders.

Content

| | | |
|----------|--|----------|
| 1 | Installation instructions for company license | |
| | System requirements | 2 |
| | Specifications for company license | 2 |
| | Installation options | 3 |
| | Installation and administrator operations using the installation wizard | 4 |
| | Initial installation | 4 |
| | Update installation | 4 |
| | Installation maintenance..... | 4 |
| | Non-guided installation and administrator operations | 5 |
| | Standalone installation | 5 |
| | Terminal Server installation | 6 |
| | Update installation | 6 |
| | License upgrade installation..... | 7 |
| | Restoring an installation (Repair)..... | 7 |
| | Uninstall..... | 8 |
| | Installation on distributed systems (MSI package)..... | 9 |
| | Transfer via a MSI database editor | 9 |
| | Transfer via command line | 10 |

1 Installation instructions for company license

In this document you will learn how to install a company license of MindReader for Outlook in your company.

System requirements Please note the following system requirements for installing MindReader for Outlook:

- ▲ Supported versions: Microsoft Outlook 2010 / 2013 / 2016
- ▲ Supported operating systems: Windows Vista SP2, Windows 7 / 8 / 8.1 / 10
- ▲ Supported protocols / mail servers: IMAP / POP3 / Microsoft Exchange / Zarafa
- ▲ Required components:
 - Microsoft .NET Framework 4.5
 - Microsoft SQL Server 2012 Express Local DB
 - Microsoft SQL Server 2012 Native Client
 - Microsoft XML Parser 4.0 SP3
 - Microsoft Visual C++ Runtime 2005 Redistributable SP1

If not available, these components are installed automatically during installation.

Information for company license For your company license of MindReader for Outlook we need the following information:

- ▲ Your email domain (e. g. `star-group.net`)
- ▲ Total number of all users of the company license

Installation options You can install and maintain your company license for MindReader for Outlook as follows:

- ▲ Using the installation wizard (⇒ [page 4](#))
- ▲ Non-guided installation using the so called “silent mode” (⇒ [page 5](#))
- ▲ Using the administrative installation package (setup_mroutlook.msi) (⇒ [page 9](#))

Please note the following:



Microsoft Outlook must be closed

Apart from the initial installation, Microsoft Outlook must be closed during all installation processes.



Installation is carried out per machine

The installation of MindReader for Outlook is carried out per machine, not per user.



Location of log file

By default, the log file `MROutlook Installation.log` is stored in the Documents library.

For the non-guided installation and administrator operations you can specify an alternative log file name and path.

Installation and administrator operations using the installation wizard

In this section you will learn how to install and maintain MindReader for Outlook using the installation wizard.

- Initial installation**
- 1 Execute the `setup_mroutlook.exe` file:
To do so, select **Run as administrator** in the context menu of the file.
 - 2 Follow the instructions of the installation wizard.
During this, enter the license number you have received from STAR.

- Update installation**
- 1 Close Microsoft Outlook.
 - 2 Execute the `setup_mroutlook.exe` file:
To do so, select **Run as administrator** in the context menu of the file.
 - 3 Follow the instructions of the installation wizard.

- Installation maintenance**
- Using the program maintenance wizard of MindReader for Outlook you can
- ▲ restore the installation (repair),
 - ▲ perform a license upgrade or
 - ▲ uninstall the program.
- 1 Close Microsoft Outlook.
 - 2 In the Windows Control Panel, open the **Programs and Features** option.
To do so, select **Start > Control Panel > Programs > Programs and Features**.
 - 3 Select MindReader for Outlook and click **Uninstall** or **Change**.
The program maintenance wizard is displayed.
 - 4 Select the desired option and follow the instructions of the maintenance wizard.

Non-guided installation and administrator operations

In this section you will learn how to install and maintain MindReader for Outlook in “silent mode” without user guidance prompts.

Using command line parameters, you can perform the following operations in so called “silent mode”, without user guidance prompts:

- ▲ Standalone installation (⇒ [page 5](#))
- ▲ Terminal Server installation (⇒ [page 6](#))
- ▲ Update installation (⇒ [page 6](#))
- ▲ License upgrade (⇒ [page 7](#))
- ▲ Repair (⇒ [page 7](#))
- ▲ Uninstall (⇒ [page 8](#))



Installation under operating systems from Windows Vista onwards

In this case, you must carry out the installation using the **Run as administrator** option. This cannot be selected from the command line. When logged in as an administrator, you therefore start a batch file containing the commands to be executed.

Standalone installation In order to carry out the initial installation on a standalone computer without user input, use the following command line parameters:

Launching with `setup_mroutlook.exe`

```
setup_mroutlook.exe /s KEY=Key string [LOG=File path]
```

The following table shows the parameter list:

| Parameter | Explanation |
|-----------|---|
| /s | Disable user guidance prompts |
| KEY | Enter the license number |
| LOG | Optional: enter an alternative log file name (full path) in inverted commas |

Command line example:

```
setup_mroutlook.exe /s
KEY=0-0-13694905-0-83000800-X-40-24077-99-1-IJFXHM-
KjIwMTQtMTtMTQqZWxzeS5zdG9semVAc3Rhcilncm91cC5uZXQ=-
1095558317
LOG="C:\Users\Public\Documents\MROutlook\Log"
```

Terminal Server installation In order to carry out the installation on a Terminal server without user input, use the following command line parameters:

Launching with setup_mroutlook.exe

```
setup_mroutlook.exe /s KEY=Key string TSERVER=TRUE
[LOG=File path]
```

The following table shows the parameter list:

| Parameter | Explanation |
|-----------|---|
| /s | Disable user guidance prompts |
| KEY | Enter the license number |
| TSERVER | TRUE must be entered for this function. |
| LOG | Optional: enter an alternative log file name (full path) in inverted commas |

Command line example:

```
setup_mroutlook.exe /s
KEY=0-0-13694905-0-83000800-X-40-24077-99-1-IJFXHM-
KjIwMTQtMTtMTQqZWxzeS5zdG9semVAc3Rhcilncm91cC5uZXQ=-
1095558317 TSERVER=TRUE
LOG="C:\Users\Public\Documents\MROutlook\Log"
```

Update installation To install an update without user input, you only need to execute the following command line parameters on the installation program for the new version. All other parameters which have been configured are ignored:

Launching with setup_mroutlook.exe

```
setup_mroutlook.exe /s [LOG=File path]
```

The following table shows the parameter list:

| Parameter | Explanation |
|-----------|---|
| /s | Disable user guidance prompts |
| LOG | Optional: enter an alternative log file name (full path) in inverted commas |

License upgrade installation To install a license upgrade without user input, you need to execute the following command line parameters on the installation program which was used to carry out the installation:



INSTALLATION PROGRAM MUST MATCH EXACTLY

The version of the installation program must be exactly the same as the one you used for carrying out the installation.

Otherwise the original installation cannot be found by the installation routine.

Launching with setup_mroutlook.exe

```
setup_mroutlook.exe /s KEY=Key string LICENSEUPG=TRUE
[LOG=File path]
```

The following table shows the parameter list:

| Parameter | Explanation |
|------------|---|
| /s | Disable user guidance prompts |
| KEY | Enter the license number |
| LICENSEUPG | TRUE must be entered for this function. |
| LOG | Optional: enter an alternative log file name (full path) in inverted commas |

Command line example:

```
setup_mroutlook.exe /s
KEY=0-0-13694905-0-83000800-X-40-24077-99-1-IJFXHM-
KjIwMTQtMTEtMTQqZWxeS5zdG9semVAc3Rhcilncm91cC5uZXQ=-
1095558317 LICENSEUPG=TRUE
```

Restoring an installation (Repair) To restore an existing installation without user input if files are lost or corrupted, execute the following command line parameters on the installation program which was used to carry out the installation:



INSTALLATION PROGRAM MUST MATCH EXACTLY

The version of the installation program must be exactly the same as the one you used for carrying out the installation.

Otherwise the original installation cannot be found by the installation routine.

Launching with setup_mroutlook.exe

```
setup_mroutlook.exe /s [LOG=File path]
```

The following table shows the parameter list:

| Parameter | Explanation |
|-----------|---|
| /s | Disable user guidance prompts |
| REPAIR | Optional: TRUE must be entered for this function. |
| LOG | Optional: enter an alternative log file name (full path) in inverted commas |

Uninstall To remove an existing installation without user input, execute the following command line parameters on the installation program which was used to carry out the installation:



INSTALLATION PROGRAM MUST MATCH EXACTLY

The version of the installation program must be exactly the same as the one you used for carrying out the installation.

Otherwise the original installation cannot be found by the installation routine.

Launching with setup_mroutlook.exe

```
setup_mroutlook.exe /s REMOVE=TRUE [REMSETTINGS=FALSE]
```

The following table shows the parameter list:

| Parameter | Explanation |
|-------------|--|
| /s | Disable user guidance prompts |
| REMOVE | TRUE must be entered for this function. |
| REMSETTINGS | By default, all selected settings and the database are removed. Optional: If all selected settings and the database should NOT be removed, REMSETTINGS=FALSE must be entered. |
| LOG | Optional: enter an alternative log file name (full path) in inverted commas |

Installation on distributed systems (MSI package)

In this section you will learn how to install MindReader for Outlook on distributed systems without user guidance using the MSI package.

With the Windows installer service, you can use the MSI package `setup_mroutlook.msi` to enable central management of the installation of MindReader for Outlook in larger distributed systems.

The required parameters you transfer via the property `CMDLINE`.

The parameters you find in the section [Non-guided installation and administrator operations](#) (⇒ [page 5](#)).

You have two options to transfer the parameters:

- ▲ via a MSI database editor (e. g. Microsoft Orca)
- ▲ via the command line



Explicitly specify installation per machine

When using the MSI package, you must explicitly specify that the installation is carried out per machine.

To do so, you must specify the parameter `ALLUSERS=TRUE` for ALL installation processes.

Transfer via a MSI database editor

Example:

```
KEY=0-0-13694905-0-83000800-X-40-24077-99-1-IJFXHM-
KjIwMTQtMTEtMTQqZWxzzeS5zdG9semVAc3Rhci1ncm91cC5uZlZQ=-
1095558317 ALLUSERS=TRUE
```

| Tables | Property | Value |
|------------------------|-----------------|---|
| AdminExecuteSequence | ProductCode | {52E53BF9-A372-419F-9025-F3309FB34B0B} |
| AdminUISequence | Manufacturer | STAR AG |
| AdvExecuteSequence | ProductLanguage | 1033 |
| Binary | UpgradeCode | {993C6DB6-EB3B-41AC-B7D9-503EB498BA62} |
| Component | ProductName | MROutlook MSI |
| CustomAction | ProductVersion | 1.0.0.60 |
| Directory | CMDLINE | KEY=0-0-13694905-0-83000800-X-40-24077-99-1-IJFXHM-KjIwMTQtMTEtMTQqZWxzzeS5zdG9semVAc3Rhci1ncm91cC5uZlZQ=-1095558317 ALLUSERS=TRUE |
| Feature | | |
| FeatureComponents | | |
| File | | |
| InstallExecuteSequence | | |
| InstallUISequence | | |
| LaunchCondition | | |
| Media | | |
| Property | | |
| Registry | | |
| _Validation | | |

**Transfer via
command line**

Example:
`msiexec /i setup_mroutlook.msi /qn CMDLINE="KEY=0-0-13694905-0-83000800-X-40-24077-99-1-IJFXHM-KjIwMTQtMTETMTQqZWxzeS5zdG9semVAc3Rhcilncm91cC5uZXQ=-1095558317 ALLUSERS=TRUE"`



Pay attention to using double quotes!

If you run the installation of the MSI package without user input and transfer the required parameters via the command line, please pay attention to using double quotes:

- ▲ double quotes around the entire content that is entered via the property `CMDLINE`
- ▲ additional double quotes around paths that have been put into double quotes because of blank spaces

STAR

Head Office of the STAR Group

STAR AG
Wiesholz 35
8262 Ramsen
Switzerland

Phone: +41 52 742 92 00

Fax: +41 52 742 92 92

E-mail: info@star-group.net

www.star-group.net

